

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions

Worldwide

MP-5102 | Single Line Analog Corded Telephone



## **Features**

#### Key:

- Dial keys (0~9,\*,#)
- Function Keys
- Speed dial keys x 2

### Phone:

- Basic Single-Line telephone system
- Fix Ringer Sound Level
- One adjustable volume switch "NORMAL, HIGH" to select the handset receiving volume level
- 2 non volatile one-touch programmable speed dial memory button
- Tone dialing only
- Hearing Aid Receiver Compliant PBX / Standard Line compatible

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.





# PRODUCT OPTIONS



MP-5102 Single-Line Analog Corded Telephone. 2 Guest Service Keys.

# **SPECIFICATIONS**

Power •Line Power (without AC adapter or battery)

Jack • Rj11 Jack x 1

•Dimensions: 220mm(L)x150mm(W)x120mm(H) (8.67"x5.91"x4.72")

• Weight: 1160g

### REGULATORY

EMI USA: FCC Part 15B

EMC EU: En55022 & En55024

PSTN USA: Part 68 EU: TBR 21

RoHS • Comply with Directive 2002/95/EC RoHS

(as amended by Commission Decision 2005/613/EC)

Temperature • Storage: Cold point at -10°C.

Hot point at +60°C.

Damp point at 80% RH, Temp at +60°C.

• **Operating:** Cold point at 0°C.

Hot point at +45°C.

Damp point at 80% RH, Temp at +45°C.





